



FEATURES

- Military QPL Approved.
- Pick-and-place compatible.

SPECIFICATIONS

- Met the requirements of MIL-PRF-83446 and MIL-STD-981, class **S** or class **B**.

Class **S** parts are intended for critical flight and mission-essential ground support applications and any application that is critical to safety.

Class **B** parts are for use in non-critical flight and non-mission-essential ground support applications.

- Operating temperature range: -55°C to +125°C
- Weight: 0.5 gram maximum.
- Inductance requirement: Tighter tolerances and other inductance values on request.
- Termination finish:
A: Gold.
F: Tin-lead.
Solderability per MIL-STD-202, Method 208.
- Outgassing: TML < 1%.

With tabs		Without tabs		Inductance ± 10% (μH)	Q Min	Q Typ	Test Freq (MHz)	SRF (min) (MHz)	DCR (max) Ohms	Current (max) (mA)
Mil Spec Dash number	C/ACM P/N	Mil Spec Dash number	C/ACM P/N							
M83446/06-01	S6001	M83446/06-25	S6025	12.0	42	50	2.5	26	2.0	110
M83446/06-02	S6002	M83446/06-26	S6026	15.0	44	52	2.5	24	2.2	105
M83446/06-03	S6003	M83446/06-27	S6027	18.0	44	52	2.5	21	2.8	100
M83446/06-04	S6004	M83446/06-28	S6028	22.0	48	55	2.5	20	3.5	85
M83446/06-05	S6005	M83446/06-29	S6029	27.0	49	57	2.5	19	4.3	75
M83446/06-06	S6006	M83446/06-30	S6030	33.0	50	58	2.5	14	5.5	68
M83446/06-07	S6007	M83446/06-31	S6031	39.0	52	60	2.5	12	6.5	61
M83446/06-08	S6008	M83446/06-32	S6032	47.0	53	62	2.5	11	8.5	54
M83446/06-09	S6009	M83446/06-33	S6033	56.0	56	64	2.5	10	12.0	46
M83446/06-10	S6010	M83446/06-34	S6034	68.0	53	62	2.5	9	13.0	42
M83446/06-11	S6011	M83446/06-35	S6035	82.0	49	57	2.5	8	15.0	40
M83446/06-12	S6012	M83446/06-36	S6036	100.0	49	57	2.5	7	18.0	36
M83446/06-13	S6013	M83446/06-37	S6037	120.0	37	45	0.79	6	21.0	34
M83446/06-14	S6014	M83446/06-38	S6038	150.0	30	38	0.79	5	26.0	31
M83446/06-15	S6015	M83446/06-39	S6039	180.0	30	38	0.79	5	28.0	29
M83446/06-16	S6016	M83446/06-40	S6040	220.0	26	32	0.79	4.5	32.0	28
M83446/06-17	S6017	M83446/06-41	S6041	270.0	26	32	0.79	4.0	36.0	26
M83446/06-18	S6018	M83446/06-42	S6042	330.0	24	30	0.79	3.7	42.0	24
M83446/06-19	S6019	M83446/06-43	S6043	390.0	24	30	0.79	3.5	46.0	23
M83446/06-20	S6020	M83446/06-44	S6044	470.0	24	30	0.79	3.0	68.0	19
M83446/06-21	S6021	M83446/06-45	S6045	560.0	22	28	0.79	2.8	77.0	18
M83446/06-22	S6022	M83446/06-46	S6046	680.0	20	26	0.79	2.5	85.0	17
M83446/06-23	S6023	M83446/06-47	S6047	820.0	16	22	0.79	2.0	100.0	16
M83446/06-24	S6024	M83446/06-48	S6048	1000.0	12	18	0.79	1.5	120.0	15

Ordering note: Add suffix "A" to C/ACM Part No. to specify Gold Plated terminations, "F" for Tin-Lead coated terminations.



COAST / ADVANCED CHIP MAGNETICS

4225 Spencer Street, Torrance CA 90503 • Phone: 310-370-8188 • Fax: 310-370-8388
 Web: <http://www.coastacm.com> • Email: sales@coastacm.com