



REVISIONS			
REV.	DESCRIPTION	DATE	BY



**Classification**

MIL-PRF-27 Grade: 6  
 MIL-PRF-27 Class: S (130° C)  
 Maximum Ambient Temperature: 105° C

**MIL-STD-981 Quality Assurance Provisions**

Class	Description	Drawing Number <sup>1</sup>
C	Commercial Parts	32356-30
B	Group A Inspection	32356-31B
E	Group A Inspection	32356-31S
S	Group A Inspection	32356-31S and
	Group B Inspection	32356-85

<sup>1</sup> The germane data will ship with the hardware.

**LOAD CONDITIONS**

Terminals	IDC A	P = I <sup>2</sup> R W
1 - 2	7.70	0.071
3 - 4	0.79	0.004
5 - 6	0.76	0.009
7 - 8	0.53	0.004
9 - 10	0.11	0.001
		P <sub>TOTAL</sub> = 0.09 W

**Electrical Characteristics**

DC Resistance: (1 - 2) = 1.2 mΩ (7 - 8) = 15 mΩ  
 (Maximum) (3 - 4) = 6.5 mΩ (9 - 10) = 44.9 mΩ  
 (5 - 6) = 16.1 mΩ

Inductance (measured at 0.1V, 10 KHz):  
 L<sub>o</sub> (1 - 2) = 4.0 μH ± 10% IDC = 0  
 (1 - 2) = L<sub>o</sub> - 10%, IDC = 7.7 A

Ratio and Polarity: (Ratios are verified with un-gapped core prior to assembly)  
 1 - 2/5 - 6 = 0.316 Nominal  
 3 - 4/5 - 6 = 0.263 Nominal  
 7 - 8/5 - 6 = 0.368 Nominal  
 9 - 10/5 - 6 = 0.947 Nominal

**These Parts Are Manufactured in Strict Compliance to MIL-STD-981.**

The "X" in the part number refers to the Quality Level (C, B, E or S), see Quality Assurance Provisions above.	UNLESS OTHERWISE SPECIFIED: Dimensions are in inches, and tolerances are:		<b>COAST/ACM</b>			
	Fractions	Decimals	Angles	TITLE <b>Coupled Inductor</b>		
	±1/64	.X = ±0.1 .XX = ±0.03 .XXX = ±0.010	±1/2°	FSCM <b>22558</b>	DWG. NO <b>32356X</b>	REV.
	DRAWN BY <b>Jim Allen</b>	DATE <b>03/21/03</b>	SCALE: none	MAX. WT.: 65 grams	SHEET 1 OF 1	