



REVISIONS			
REV.	DESCRIPTION	DATE	BY



Classification

MIL-PRF-27 Grade: 6
 MIL-PRF-27 Class: S (130° C)
 Maximum Ambient Temperature: 105° C

MIL-STD-981 Quality Assurance Provisions

Class	Description	Drawing Number ¹
C	Commercial Parts	32377-30
B	Group A Inspection	32377-31B
E	Group A Inspection	32377-31S
S	Group A Inspection	32377-31S and
	Group B Inspection	32377-85

¹ The germane data will ship with the hardware.

LOAD CONDITIONS

Terminals	I _{DC} A	P = I ² R W
1 - 2	2.52	0.029
3 - 4	2.02	0.065
5 - 6	0.38	0.015
7 - 8	1.21	0.047
9 - 10	0.16	0.005
		P _{TOTAL} = 0.161 W

Electrical Characteristics

DC Resistance: (1 - 2) = 4.6 mΩ (7 - 8) = 32 mΩ Ratio and Polarity: (Ratios are verified with un-gapped core prior to assembly)
 (Maximum) (3 - 4) = 16 mΩ (9 - 10) = 198 mΩ
 (5 - 6) = 103 mΩ
 Inductance (measured at 0.1V, 10 KHz):
 (1 - 2) = 11 μH ± 25% I_{DC} = 0
 (1 - 2) = 7.7 μH Minimum, I_{DC} = 12A
 1 - 2/5 - 6 = 0.250 Nominal
 1 - 2/9 - 10 = 0.250 Nominal
 3 - 4/9 - 10 = 0.500 Nominal
 7 - 8/9 - 10 = 0.500 Nominal

These Parts Are Manufactured in Strict Compliance to MIL-STD-981.

The "X" in the part number refers to the Quality Level (C, B, E or S), see Quality Assurance Provisions above.	UNLESS OTHERWISE SPECIFIED: Dimensions are in inches, and tolerances are:		COAST/ACM			
	Fractions	Decimals	Angles	TITLE		
	±1/64	.X = ±0.1 .XX = ±0.03 .XXX = ±0.010	±1/2°	Coupled Inductor		
	DRAWN BY	DATE	FSCM	DWG. NO	REV.	
DO NOT SCALE DRAWING	Jim Allen	04/28/03	22558	32377X		
		SCALE: none	MAX. WT.: 65 grams	SHEET 1 OF 1		