

LOAD CONDITIONS

 $E(1-2) = 20V_{RMS}, 2000 Hz$ $P_{TOTAL} < 0.8W$

Classification


MIL-PRF-27 Grade:

MIL-PRF-27 Class: S (130° C) Maximum Ambient Temperature: 105° C

MIL-STD-981 Quality Assurance Provisions

Class	Description	Drawing Number 1
C	Commercial Parts	33046-30
В	Group A Inspection	33046-31B
E	Group A Inspection	33046-31S
S	Group A Inspection	33046-31S and
	Group B Inspection	33046-85
1 701	1 . 91 1 .	1.1 .1 1 1

¹ The germane data will ship with the hardware.



DATE

Black Arrow denotes direction of current flow.

Electrical Characteristics

DC Resistance: $(1 - 2) = 190 \Omega$ Maximum

 $(3 - 4) = 100 \Omega$ Maximum


Volt-Seconds: (1-2) = 10 mV-Sec Minimum, measured at 1500 Hz, Ipk = 100 mA \pm 10%, Rs = 20 Ω

Evidence of core matching per 33046-94 shall accompany each shipment Core Matching:

Transfer Characteristics: Per Sheet 2

These Parts Are Manufactured in Strict Compliance to MIL-STD-981.

The "X" in the part number refers to the Quality Level	UNLESS OTHERWISE SPECIFIED: Dimensions are in inches, and			COAST/ACM				
(C, B, E, or S), see Quality Assurance Provisions	tolerances are: Fractions Decima .X = ±0.1 ±1/64 .XX = ±0.0		ais Angles	Transformer, Current Monitor				
above.	.x	XX=±0.010	0	FSCM		DWG. NO		REV.
	DRAWN B	Y	DATE	2255	8	33	046X	
DO NOT SCALE DRAWING	Jim Allen		09/24/03	SCALE: none	MA	XX. WT.: 25 grams	SHEET	1 OF 1



Transfer Characteristics:	<u>Ic (A)</u>	<u>Ec (V)</u>
Set Ein = 20 V (peak Square Wave) at 3000 Hz	0	0 - 0.020
	+10	0.622 - 0.660
Note: Winding 3 - 4 has no connections	+20	1.261 - 1.339
Route one turn Ic cable > 6" from core, before and after going through the	+30	1.894 - 2.012
core.	+40	2.518 - 2.674
	+50	3.114 - 3.306
Select and record the value of R _L for best transfer characteristics curve from the	+60	3.719 - 3.949
following values:	+70	4.298 - 4.564
185Ω , 187Ω , 189Ω , 190Ω , 192Ω , 194Ω , 196Ω , 198Ω , 200Ω , or 202Ω	+80	4.850 - 5.150

	UNLESS OTHERWISE SPECIFIED: Dimensions are in inches, and			COAST/ACM			
	tolerances are:		TITLE				
	Fractions	Decimals	Angles	Power Transformer			rmer
	±1/64	$.XX = \pm 0.03$ $.XXX = \pm 0.010$	±5°	FSCM		DWG. NO	
	DRAWN BY DATE		22558		33046X		
DO NOT SCALE	Jim	Allen	09/24/03	SCALE: 1	none	·	SHEET 2 OF 2