


REVISIONS			
REV.	DESCRIPTION	DATE	BY

Mark on Top:
 White dot for Pin 1
 22558-32303X
 S/N XXX
 Date Code



Coplanarity pad to pad is 0.003 max. (by design only, prior to solder coating, not inspectible).

Classification

MIL-PRF-27 Grade: 5
 MIL-PRF-27 Class: S (130° C)
 Maximum Ambient Temperature: 105° C

MIL-STD-981 Quality Assurance Provisions

Class	Description	Drawing Number
C	Commercial Parts	32303-30
B	Group A Inspection	32303-31B
E	Group A Inspection	32303-31S
S	Group A Inspection	32303-31S and
	Group B Inspection	32303-85

LOAD CONDITIONS	
IDC = 5.0A	PTOTAL < 0.2 W

Electrical Characteristics

DC Resistance: (1 - 2) = 6.0 mΩ Maximum
 (3 - 4) = 6.0 mΩ Maximum
 Inductance (measured at 0.1 V, 10 KHz):
 (1+4 - 2+3) = 1.98 μH +40%, -10%, IDC = 0 A
 (1+4 - 2+3) = 0.28 μH Minimum, IDC = 5.0 A

These Parts Are Manufactured in Strict Compliance to MIL-STD-981.

The "X" in the part number refers to the Quality Level (C, B, E, or S), see Quality Assurance Provisions above.	UNLESS OTHERWISE SPECIFIED: Dimensions are in inches, and tolerances are:		COAST/ACM		
	Fractions ±1/64	Decimals .XX = ±0.03 .XXX = ±0.010	Angles ±1/2°	TITLE Inductor	
	DRAWN BY Jim Allen	DATE 08/20/02	FSCM 22558	DWG. NO 32303X	REV.
DO NOT SCALE DRAWING		SCALE: none	MAX. WT.: 4 grams	SHEET 1 OF 1	