


S96000 Series

MIL-STD-981, MIL-PRF-27/372

Power Inductors

QPL Approved




Marking (on top of the case)


M27/372-(Dash Number)

22558


S96xxx



SERIES MODE



PARALLEL MODE



Physical Parameters				Tape & Reel (additional charge)	
Size	E Max.	F Max.	G	Small Reel (Qty)	Large Reel (Qty)
A	0.260 (6.60)	0.230 (5.84)	0.085 ± .010 (1.90 to 2.42)	300	1000
B	0.410 (10.41)	0.230 (5.84)	0.135 ± .010 (3.17 to 3.69)	200	650
C	0.410 (10.41)	0.310 (7.87)	0.135 ± .010 (3.17 to 3.69)	200	650
D	0.535 (13.59)	0.310 (7.87)	0.200 ± .010 (4.82 to 5.34)	125	300

ALL DIMENSIONS ARE IN INCHES, () MM.

FEATURES

- Leadless device for minimum footprint
- Lead Pad Coplanarity Max: 0.002 inches; 0.05 mm
- Low EMI Radiation
- Low Thermal Expansion permits mounting on most substrate materials
- Custom Designs: Other electrical configurations and performance characteristics are available in various sizes and package types

SPECIFICATIONS

- Case: Grade 5, encapsulated
- Terminals: tin-lead plated phosphor bronze
- Weight: 1.25 ounces, maximum
- Altitude: 70,000 feet, maximum
- Operating temperature range: -55°C to 125°C
- Insulation Resistance: MIL-STD-202, method 302, 1,000 megohms minimum at 100 V dc
- Terminal strength: MIL-STD-202, method 211, test condition A, 2 lbs
- Dielectric withstanding voltage (at sea level): 200 volts rms
- Temperature rise 35°C max over ambient temperature of 90°C
- Terminals meet solderability per MIL-STD-202, Method 208
- Inductance measured at 0.1 Vrms, 10 kHz, 0 DC current
- Outgassing meets NASA spec SP-R-0022A: TML < 1%
- Meets the requirements of MIL-PRF-27/372 and MIL-STD-981, class S or class B Class S parts are intended for critical flight and mission-essential ground support applications and any application that is critical to safety. Class B parts are for use in noncritical flight and non-mission-essential ground support applications.

Part or Identifying Number (PIN):

S96xxxS: MIL-STD-981, Class S
S96xxxB: MIL-STD-981, Class B

Dash Number	C/ACM P/N	Series			Parallel			Size	Power Rating (mW)
		Inductance ±10 Percent (mH)	Rated DC Current (mA)	DC Resistance Max (Ω)	Inductance ±10 percent (mH)	Rated DC Current (mA)	DC Resistance Max (Ω)		
MIL-PRF-27/372-001	S96001	0.100	300	1.60	0.025	600	0.400	A	125
MIL-PRF-27/372-002	S96002	0.100	600	0.96	0.025	1200	0.240	B	250
MIL-PRF-27/372-003	S96003	0.100	780	0.37	0.025	1560	0.093	C	300
MIL-PRF-27/372-004	S96004	0.100	1350	0.21	0.025	2700	0.053	D	450
MIL-PRF-27/372-005	S96005	0.250	200	3.11	0.062	400	0.778	A	125
MIL-PRF-27/372-006	S96006	0.250	400	1.98	0.062	800	0.495	B	250
MIL-PRF-27/372-007	S96007	0.250	530	0.82	0.062	1060	0.205	C	300
MIL-PRF-27/372-008	S96008	0.250	930	0.41	0.062	1860	0.103	D	450
MIL-PRF-27/372-009	S96009	0.500	150	6.14	0.125	300	1.535	A	125
MIL-PRF-27/372-010	S96010	0.500	300	3.35	0.125	600	0.838	B	250
MIL-PRF-27/372-011	S96011	0.500	380	1.62	0.125	760	0.405	C	300
MIL-PRF-27/372-012	S96012	0.500	660	0.82	0.125	1320	0.205	D	450
MIL-PRF-27/372-013	S96013	0.750	120	9.45	0.187	240	2.363	A	125
MIL-PRF-27/372-014	S96014	0.750	250	5.20	0.187	500	1.300	B	250
MIL-PRF-27/372-015	S96015	0.750	310	2.50	0.187	620	0.625	C	300
MIL-PRF-27/372-016	S96016	0.750	540	1.25	0.187	1080	0.313	D	450
MIL-PRF-27/372-017	S96017	1.000	95	12.85	0.250	190	3.213	A	125
MIL-PRF-27/372-018	S96018	1.000	200	6.90	0.250	400	1.725	B	250
MIL-PRF-27/372-019	S96019	1.000	270	3.37	0.250	540	0.843	C	300
MIL-PRF-27/372-020	S96020	1.000	470	1.87	0.250	940	0.468	D	450
MIL-PRF-27/372-021	S96021	2.000	75	25.60	0.500	150	6.400	A	125
MIL-PRF-27/372-022	S96022	2.000	150	12.20	0.500	300	3.050	B	250
MIL-PRF-27/372-023	S96023	2.000	190	6.75	0.500	380	1.690	C	300
MIL-PRF-27/372-024	S96024	2.000	330	3.62	0.500	660	0.910	D	450
MIL-PRF-27/372-025	S96025	3.000	60	38.40	0.750	120	9.600	A	125
MIL-PRF-27/372-026	S96026	3.000	120	18.30	0.750	240	4.580	B	250
MIL-PRF-27/372-027	S96027	3.000	160	10.12	0.750	320	2.530	C	300
MIL-PRF-27/372-028	S96028	3.000	270	5.50	0.750	540	1.380	D	450
MIL-PRF-27/372-029	S96029	5.000	45	64.00	1.250	90	16.000	A	125
MIL-PRF-27/372-030	S96030	5.000	90	30.40	1.250	180	7.600	B	250
MIL-PRF-27/372-031	S96031	5.000	120	16.87	1.250	240	4.220	C	300
MIL-PRF-27/372-032	S96032	5.000	210	9.12	1.250	420	2.280	D	450
MIL-PRF-27/372-033	S96033	7.500	30	96.00	1.875	60	24.000	A	125
MIL-PRF-27/372-034	S96034	7.500	70	46.00	1.875	140	11.500	B	250
MIL-PRF-27/372-035	S96035	7.500	100	25.37	1.875	200	6.350	C	300
MIL-PRF-27/372-036	S96036	7.500	170	13.75	1.875	340	3.440	D	450
MIL-PRF-27/372-037	S96037	10.000	20	128.00	2.500	40	32.000	A	125
MIL-PRF-27/372-038	S96038	10.000	50	61.00	2.500	100	15.250	B	250
MIL-PRF-27/372-039	S96039	10.000	80	33.75	2.500	160	8.440	C	300
MIL-PRF-27/372-040	S96040	10.000	140	18.25	2.500	280	4.570	D	450



Coast / Advanced Chip Magnetics

4225 Spencer Street, Torrance CA 90503 · Phone 310-370-8188 · Fax 310-370-8388

Web: www.coastacm.com · Email: sales@coastacm.com